
Product Description: **Transparent, static Premium**

Description

Material:	PVC, monomeric calendered film	
Thickness:	150 ± 7 µm bzw. 0,11 ± 0,007 mm (without protective sheet)	
Weight:	200 g/m ² ± 7% (without protective sheet)	
Backing protective sheet:	transparent polyester film, 75 µm, without printing	
Variations:	Long roll 45 cm: 15 m	Short roll 45 cm: 1,5 m
	Long roll 67,5 cm: 15 m	Short roll 67,5 cm: 1,5 m
	Long roll 90 cm: 15 m	Short roll 90 cm: 1,5 m
Packaging:	<ul style="list-style-type: none">▪ Shrunk with a PE-foil▪ Standard label for long roll and short roll (176 x 102 mm) with the following languages: D, GB, FR, I, ES, CZ, PL, NL (8 languages) Label is placed in the middle of the roll and carries reference number, barcode and date of production.▪ In addition a picture of each single product and the according application are printed on the different labels for each design▪ The packaging carton is printed and equipped with a white label containing reference number, barcode and quantity.	
Packaging unit:	Number of rolls per carton (=VE)	
	Long roll 45 cm: 6	Short roll 45 cm: 7
	Long roll 67,5 cm: 3	Short roll 67,5 cm: 7
	Long roll 90 cm: 3	Short roll 90 cm: 7
Product characteristics:	Decorative static cling film with privacy protection (adheres without adhesive); static Premium protects against skin-damaging UVA rays and prevents bleaching of objects e.g. furniture while absorbing UVB-rays (at least 95% UV-protection); easily removable (leaves no residue); reusable; simple and fast to use.	

Product Features static PREMIUM vs. common static cling films

- Once more optimized adhesion (smoother back side)
- Even more easy to apply (because of the thicker film)
- Premium haptics (deeper embossing)
- Noble optic due to satined surface
- Protected surface because of additional protective laquer
- Modern designs in unobtrusive optic

Storage

Cool and dry at room temperature (23 °C ± 2 °C). Avoid direct sunlight. The temperature should not exceed 40 °C on a permanent basis.

The company Konrad Hornschuch AG is certified after DIN EN ISO 9001, VDA 6.1 and QS 9000. We are producer of high-quality products.

All statements are based on our current knowledge and experience. Due to the variety of possible influences when processing our products we suggest to carry out individual tests. A legally obligatory warranty of characteristics cannot be derived.

Stand: März 12

